50 kVA Distribution Transformer



Brand: Datsan Product Code: DT50 Availability: 2 - 3 Days Weight: 490.00kg Dimensions: 760.00mm x 360.00mm x 670.00mm

Description

We generally manufacture distribution transformers in this power range, mainly in two different types:

- 1. Transformer with conservator tank (WCT),
- 2. Hermetically sealed type (HST),

Below table will help to engineers to select the best option according to environmental conditions which transformer works in:

	High	High Altitude	Rural	High	Over Load	Unstable
	Environmental		Network	Humidity	Conditions	Loading
	Temperature			-		_
WCT	Î	↑	\Downarrow	\Downarrow	€	€
WCT HST	\Downarrow	\Downarrow	↑	↑	\Downarrow	\Downarrow
Meanwhile here is the advantage-disadvantage of the WCT-HST types:						

- In HST type, tank pressure is more than WCT type. WCT type generally works under low pressure due to its open to atmosphere,
- In HST type, cooling/insulation oil does not contact to the air (theoretically). Therefore oil maintenance period is longer than WCT type,
- HST type transformers and their related parts generally work under higher

Specification					
General Information					
Power (kVA)	50				
Input Voltage (kV)	from 6.3 upto 36				
Output Voltage (V)	400-410-416-431 or as per requested voltage				
Туре	With conservator tank or hermetically sealed				
Mounting Type	Pad or pole mounted				
Origin	Turkey				
Technical Datas					
Max. Environmental	50				
Temperature (°C)					
Max. Altitude (m)	As per customer request				
Magnetic Circuit Type	Core Type				
Magnetic Circuit Material	CRGO (Cold-Rolled Grain Oriented silicon steel)				
Coils					
Winding Material	Copper and/or Aluminum				
Coil Geometry	Round or oval				
Transformer Tank					
Cooling Type	ONAN or KNAN				
Cooling Surface	Corrugated wall				
Surface Protection	Paint or Galvanizing				
Product Gallery					





